



Wall Lamp

ELX-XMY



3.000K 4.000K 5.000K 6.000K

■ Specification

Daya (W)	Input Voltage	Frequency Amp	LED Efikasi	Total Lumen	CRI	Temperatur Warna	Proteksi	Material
6W	AC100-240V	50/60Hz	80Lm/W	480Lm	>80Ra (<i>>90Ra Optional</i>)	3000K/4000K/6000K	IP65	Die Casting Aluminium
10W	AC100-240V	50/60Hz	80Lm/W	800Lm	>80Ra (<i>>90Ra Optional</i>)	3000K/4000K/6000K	IP65	Die Casting Aluminium
20W	AC100-240V	50/60Hz	80Lm/W	1.600Lm	>80Ra (<i>>90Ra Optional</i>)	3000K/4000K/6000K	IP65	Die Casting Aluminium
30W	AC100-240V	50/60Hz	80Lm/W	2.400Lm	>80Ra (<i>>90Ra Optional</i>)	3000K/4000K/6000K	IP65	Die Casting Aluminium

Model : ELX-XMY-03WX2



Dimension (mm)



Model : ELX-XMY-05WX2



Dimension (mm)



Model : ELX-XMY-10WX2



Dimension (mm)



Model : ELX-XMY-15WX2



Dimension (mm)



Application



* Easy maintenance

- Modular LED for easy replacement
- Opening and closing possible of LED module part and power supply part
- Customizable beam angle
- Temperature max 50°