



WALL LAMP



ECO
UXON

Wall Lamp

ELX-WL



Body Color



■ Specification

Daya (W)	Input Voltage	Frequency Amp	LED Efikasi	Total Lumen	CRI	Temperatur Warna	Proteksi	Material
3W	AC100-240V	50/60Hz	80lm/W	240Lm	>80Ra (-90Ra Optional)	3000K/4000K/6000K	IP65	Die Casting Aluminium
6W	AC100-240V	50/60Hz	80lm/W	480Lm	>80Ra (-90Ra Optional)	3000K/4000K/6000K	IP65	Die Casting Aluminium
12W	AC100-240V	50/60Hz	80lm/W	960Lm	>80Ra (-90Ra Optional)	3000K/4000K/6000K	IP65	Die Casting Aluminium
18W	AC100-240V	50/60Hz	80lm/W	1.440Lm	>80Ra (-90Ra Optional)	3000K/4000K/6000K	IP65	Die Casting Aluminium
24W	AC100-240V	50/60Hz	80lm/W	1.920Lm	>80Ra (-90Ra Optional)	3000K/4000K/6000K	IP65	Die Casting Aluminium

Model : ELX-WL65160-03WX1



Dimension (mm)



Model : ELX-WL90160-06WX1




Dimension (mm)



Model : ELX-WL11020-12WX1




Dimension (mm)



Model : ELX-WL145200-18WX1




Dimension (mm)



Model : ELX-WL160200-24WX1



Dimension (mm)



Application



* Easy maintenance

- Modular LED for easy replacement
- Opening and closing possible of LED module part and power supply part
- Customizable beam angle
- Temperature max 50°

