



# DOWN LIGHT

Indoor Light | Downlight



## Downlight Ecoluxon

### ELX-DL-SMD



3.000K    4.000K    5.000K    6.000K


## ■ Specification

Daya (W)	Input Voltage	Frequency Amp	LED Efikasi	Total Lumen	CRI	Temperatur Warna	Proteksi	Berat	Material
6W	AC165-265V	50/60Hz	110Lm/W	660Lm	>80Ra	3000K/4000K/6000K	IP20	80gr	Aluminium Alloy
9W	AC165-265V	50/60Hz	110Lm/W	990Lm	>80Ra	3000K/4000K/6000K	IP20	110gr	Aluminium Alloy
12W	AC165-265V	50/60Hz	110Lm/W	1.320Lm	>80Ra	3000K/4000K/6000K	IP20	150gr	Aluminium Alloy
18W	AC165-265V	50/60Hz	110Lm/W	1.980Lm	>80Ra	3000K/4000K/6000K	IP20	210gr	Aluminium Alloy


Model : ELX-DL-SMD-5W



Dimension ( mm )




Light Distribution Curve




Model : ELX-DL-SMD-9W



Dimension ( mm )




Light Distribution Curve




Model : ELX-DL-SMD-12W



Dimension ( mm )




Light Distribution Curve




Model : ELX-DL-SMD-18W



Dimension ( mm )



Light Distribution Curve



\* Easy maintenance

- Modular LED for easy replacement
- Opening and closing possible of LED module part and power supply part
- Customizable beam angle
- Temperature max 50°

