



## ZERON

NEW LIGHT NEW LIFE

### Downlight Surface Mounted

### ZERN-J02



3.000K    4.000K    5.000K    6.000K


## ■ Specification

Daya (W)	Input Voltage	Frequency Amp	LED Efikasi	Total Lumen	CRI	Temperatur Warna	Proteksi	Beam Angle	Material
12W	AC110-240V	50/60Hz	100Lm/W	1.200Lm	>80Ra	3000K/4000K/5000K/6000K	IP20	20°/40°/60°	Die Casting Aluminium
20W	AC110-240V	50/60Hz	100Lm/W	2.000Lm	>80Ra	3000K/4000K/5000K/6000K	IP20	20°/40°/60°	Die Casting Aluminium
30W	AC110-240V	50/60Hz	100Lm/W	3.000Lm	>80Ra	3000K/4000K/5000K/6000K	IP20	20°/40°/60°	Die Casting Aluminium

Model : ZERN-J02-2005T-12W




Dimension ( mm )



Model : ZERN-J02-3001T-20W




Dimension ( mm )



Model : ZERN-J02-4001T-30W



Dimension ( mm )



- \* Easy maintenance
- Modular LED for easy replacement
- Opening and closing possible of LED module part and power supply part
- Customizable beam angle
- Temperature max 50°