



ZERON

NEW LIGHT NEW LIFE

Recessed Downlight

ZERN-H06R



3.000K 4.000K 5.000K 6.000K


Specification

Daya (W)	Input Voltage	Frequency Amp	LED Efikasi	Total Lumen	CRI	Temperatur Warna	Proteksi	Beam Angle	Material
10W	AC100-277V	50/60Hz	100Lm/W	1.000Lm	>80Ra <i>Optional (>90Ra, >95Ra)</i>	3000K/4000K/5000K/6000K	IP65	60°	Die Casting Aluminium
20W	AC100-277V	50/60Hz	100Lm/W	2.000Lm	>80Ra <i>Optional (>90Ra, >95Ra)</i>	3000K/4000K/5000K/6000K	IP65	60°	Die Casting Aluminium
30W	AC100-277V	50/60Hz	100Lm/W	3.000Lm	>80Ra <i>Optional (>90Ra, >95Ra)</i>	3000K/4000K/5000K/6000K	IP65	60°	Die Casting Aluminium
40W	AC100-277V	50/60Hz	100Lm/W	4.000Lm	>80Ra <i>Optional (>90Ra, >95Ra)</i>	3000K/4000K/5000K/6000K	IP65	60°	Die Casting Aluminium

Model : ZERN-H06R-10W




Dimension (mm)



Model : ZERN-H06R-30W




Dimension (mm)



Model : ZERN-H06R-20W




Dimension (mm)



Model : ZERN-H06R-40W



Dimension (mm)



* Easy maintenance

- Modular LED for easy replacement
- Opening and closing possible of LED module part and power supply part
- Customizable beam angle
- Temperature max 50°

