



DOWN LIGHT

Indoor Light | Downlight

ZERON

NEW LIGHT NEW LIFE

Recessed Downlight

ZERN-Y01KZS



3.000K 4.000K 5.000K 6.000K


■ Specification

Daya (W)	Input Voltage	Frequency Amp	LED Efikasi	Total Lumen	CRI	Temperatur Warna	Proteksi	Material
12W	AC100-240V	50/60Hz	100Lm/W	1.200Lm	>80Ra <i>Optional (>90Ra >95Ra)</i>	3000K/4000K/5000K	IP20	Die Casting Aluminium
24W	AC100-240V	50/60Hz	100Lm/W	2.400Lm	>80Ra <i>Optional (>90Ra >95Ra)</i>	3000K/4000K/5000K	IP20	Die Casting Aluminium
36W	AC100-240V	50/60Hz	100Lm/W	3.600Lm	>80Ra <i>Optional (>90Ra >95Ra)</i>	3000K/4000K/5000K	IP20	Die Casting Aluminium
48W	AC100-240V	50/60Hz	100Lm/W	4.800Lm	>80Ra <i>Optional (>90Ra >95Ra)</i>	3000K/4000K/5000K	IP20	Die Casting Aluminium

Model : ZERN-Y01KZS-12*1




Dimension (mm)



Model : ZERN-Y01KZS-12*3




Dimension (mm)



Model : ZERN-Y01KZS-12*2




Dimension (mm)



Model : ZERN-Y01KZS-12*4



Dimension (mm)



* Easy maintenance

- Modular LED for easy replacement
- Opening and closing possible of LED module part and power supply part
- Customizable beam angle
- Temperature max 50°

