



TUBE LIGHT

Indoor Light | Tube Light



Tube Light Ecoluxon

ELX-T5



- 3.000K
- 4.000K
- 5.000K
- 6.000K



■ Specification

Daya (W)	Input Voltage	Frequency Amp	LED Efikasi	Total Lumen	CRI	Temperatur Warna	Proteksi	Berat	Material
4W	AC100-240V	50/60Hz	110Lm/W	440Lm	>80Ra	3000K/6000K	IP20	42gr	Nano PC Cover
8W	AC100-240V	50/60Hz	110Lm/W	880Lm	>80Ra	3000K/6000K	IP20	65gr	Nano PC Cover
12W	AC100-240V	50/60Hz	110Lm/W	1.320Lm	>80Ra	3000K/6000K	IP20	96gr	Nano PC Cover
16W	AC100-240V	50/60Hz	110Lm/W	1.760Lm	>80Ra	3000K/6000K	IP20	118gr	Nano PC Cover


Model : ELX-T5300-ECOSM-4W



Dimension (mm)





Light Distribution Curve




Model : ELX-T5600-ECOSM-8W



Dimension (mm)





Light Distribution Curve




Model : ELX-T5900-ECOSM-12W



Dimension (mm)





Light Distribution Curve




Model : ELX-T51200-ECOSM-16W



Dimension (mm)



Light Distribution Curve



* Easy maintenance

- Modular LED for easy replacement
- Opening and closing possible of LED module part and power supply part
- Customizable beam angle
- Temperature max 50°

